

OAsys® INTERNAL PLANT
OTIAN ASDH Auxiliary Shelf 3A
Part Number: XEXSC00423 BT Item Code: 023901



Description

- Allows termination of up to 12 fibres.
- Supplied as one unit containing 2 splice modules. Each module houses 2 splice trays.
- Suitable for Splicing 3 Fibres per Splice Tray.
- Suitable for 19" or ETSI rack mounting practice.
- SPACE ENVELOPE: 535mm x 230mm x 44mm (W x D x H).

Tools & Additional Items Required

Additional Items Required:	Prysmian Part No.	BT Item Code
Splice protectors 4A	XPESC00053	075110
Restraint Kit 2A	XAPSC00546	075869
Fixings:	No fixings required	
Tools:	Pozi Drive Screwdriver No.2, 24mm Spanner, BT Stripper Fibre 3A.	

Component Parts (pictures not to scale)

1 Splice Shelf Assembly Qty 1 	2 Installation Kit Qty 1  For Contents refer to Numbers 3 to 9 below.	
3 Screw M6 x 12mm Pozi Pan Hd. Qty 8 6 Cable Ties. Qty 2	4 M6 Cage Nuts Qty 4 7 ETSI Adapter Mounting Brackets. Qty 2	5 M6 Nylon 6 Washers Qty 8 8 Portex Tube Qty 1mtr

12 Fibre Cable Installation


Step 1

PREPARATION STEP

- Prior to installation ensure that there is a minimum of 4m of cable spare for installation, termination, and storage purposes.

12 Fibre Cable Installation


Step 2



- Identify the 2-way manifold. Remove clear plastic cover from the manifold exposing the two channels.

12 Fibre Cable Installation


Step 3



- Temporarily remove the 2-way manifold and tubes from its fixed position by removing the fixing screw.

12 Fibre Cable Installation


Step 4



- Slacken Cable Gland and thread cable through.
- Measure 3m from end of cable and mark the sheath. This will be the 'Cable Butt'.

12 Fibre Cable Installation


Step 5



- Remove sheath from the 'Butt Mark' to expose the cable elements. Remove unwanted cable elements at the butt.
- Cut the Central Strength Member (CSM) to a length of 100mm from the cable butt.

12 Fibre Cable Installation

Step 6



- Make a mark on the single 12 Fibre cable element 30mm from the cable butt.
- Use a **BT Stripper Fibre 3A** to remove the protective tube/sheath from the element back to this mark to expose the fibres.

Align element vertically with bottom of gland.

CSM

- Slide cable back through the cable gland until the ‘Butt’ is in line with the end of the cable gland.
- Feed the CSM through the slot in the sidewall.
- Align cable in gland such that single cable element is positioned at the bottom of the cable gland under the CSM.
- Tighten cable gland to anchor cable using an appropriate spanner.

12 Fibre Cable Installation

Step 8



- Secure the CSM to the sidewall using the 2 cable ties (6). Remove excess length of cable ties using a ‘flush cutter’.

12 Fibre Cable Installation

Step 9




- Carefully refit the two-way manifold and tubes removed in Step3.
- Temporarily store the exposed fibres.
- Select the 12 fibres from the cable element and split these into 2 groups of 6.
- Feed the first group of 6 Fibres into the Yellow Bend Limiting Tube (BLT).

NOTE: The Fibre Colours in each group will be as directed by the BT planner.

12 Fibre Cable Installation


Step 10



- Fully open the lower Splice Module.
- Open both splice tray covers. Remove the sliding cover of the Splice Module to reveal the fibre tracks and the fibre-guiding pin.

12 Fibre Cable Installation


Step 11



- Continue feeding the first group of 6 fibres until they exit the blue tube. Remove fibres using the guide pin and pull fibres through.

12 Fibre Cable Installation


Step 12



- Continue feeding fibres onto the Splice Module, along the track, and under the first two track bridges.

12 Fibre Cable Installation

Step 13




- Segregate the 6 fibres into 2 groups of 3 fibres. Route the first group onto splice tray No.1 (Nearest the Pivot Bush).
- Route the fibres anti-clockwise $\frac{1}{2}$ a turn around the tray, through the 'S' Track and coil within the tray storage area for later use.

NOTE: The Fibre Colours in each group routed to the Splice Tray will be as directed by the BT planner.

12 Fibre Cable Installation

Step 14



- Route the second group of 3 fibres through the outer track and onto Splice Tray 2 (nearest the user).
- Coil and store fibres as for tray 1.
- Check that all fibres are within their respective tracks.
- Replace all covers.

NOTE: The Fibre Colours in each group will be as directed by the BT planner.

12 Fibre Cable Installation


Step 15



- Fully open the top splice module and feed the remaining group 6 fibres into the Green BLT. Continue feeding the fibres until they appear out of the blue tube.
- Repeat **Steps 11 to 14** for fibres inserted into the Green BLT.

12 Fibre Cable Installation


Step 16



- If the sub rack is to be used in an ETSI front mounted rack, fit the 2 conversion brackets (7) using 4, M6 x 12mm screws (3) and 4, M6 Nylon Washers (5).

12 Fibre Cable Installation

Step 17



- Select the rack mounting position for the shelf and fit 4 Cage nuts **(4)** into the rack uprights.

NOTE: The lower cage nut is fitted in the second location hole from the bottom of the mounting rail.

12 Fibre Cable Installation


Step 18



- Using 4, M6 x 12mm screws (3) and 4, Nylon Washers (5) fit shelf and cable in position.

Prysmian
Group
INSTALLATION INSTRUCTION
COF8001 Jumper Installation


Step 19



- Fully open both modules.
- Feed the **First Pair** of jumpers down the rack and under the rear bend manger on the splice shelf.
- Continue feeding the jumpers through until approximately 2.0m of jumper have been threaded through.

COF8001 Jumper Installation


Step 20



- Close the top module.
- Feed the jumper cables around the channel until they protrude from the front of the Splice Module. Ensure that the jumper cables are correctly located under the three channel bridges.
- Pull 2 metres of cable through to the front of the Splice Module.
- Temporarily close the module to set length of jumpers.

COF8001 Jumper Installation


Step 21



- Apply a butt mark to the 2 jumpers in accordance with its planned position within the Splice Module (**Position No. 1**). Positions 1 and 2 are for routing to splice tray 1 and positions 3 and 4 are for routing to splice tray 2.
- Strip and prepare fibre in accordance with IP008 – Assembly of 2 jumpers into one restraint.

Prysmian
Group
INSTALLATION INSTRUCTION
COF8001 Jumper Installation


Step 22



- Locate the restraint (**containing the 2 Jumpers**) in to Position No.1 on the Splice Module.
- Route the 2 fibres through the tracks and on to Splice Tray No. 1.

COF8001 Jumper Installation


Step 23



- Repeat Steps 19 and 20, this time for a single jumper.
- Apply a butt mark to the jumper cable in accordance with its planned position within the Splice Module **(Position No. 2)**. Positions 1 and 2 are for routing to splice tray 1 and positions 3 and 4 are for routing to splice tray 2.
- Strip and prepare fibre in accordance with IP008 – Assembly of 1 jumper into one restraint.

COF8001 Jumper Installation


Step 24



- Locate the restraint (**containing the single Jumper**) in to Position No.2 on the Splice Module.
- Route the single fibre through the tracks and on to Splice Tray No. 1.

COF8001 Jumper Installation

Step 25



- Follow Steps 19 to 24 for the next three jumper cables.
- **Position the double jumpers in Position 3 and the single jumper in Position 4.**
- Route the three fibres onto Splice Tray No. 2.
- Check fibre routing and ensure that all covers have been replaced on the splice trays and module.

Prysmian
Group
INSTALLATION INSTRUCTION
COF8001 Jumper Installation

Step 26




- Close the Lower Splice Module.
- Repeat Steps 19 to 24 for the Top Splice Module.
- Check fibre routing and ensure that all covers have been replaced on the splice trays and module.
- Close the top Splice Module.

Splicing

Step 27

**Primary coated
fibres from BF
Bundle**



**Secondary Coated
fibres from pre-
installed pigtail.**




- Carefully uncoil all fibres from the storage area.
- Separate the primary coated fibres from the secondary coated fibres and safely store fibres for splicing.
- Splice fibres.

NOTE: Each splice tray will have three splices. Primary Fibre colours to be spliced to the COF8001 Jumpers will be as directed by the Planner.

Splicing

Step 28



- Place splice protector in storage bay.
- Ensure splice protector has been pushed down to the lowest available position in the storage bay. Repeat for remaining fibre.

Splicing

Step 29

**Fold loops
into splice
tray**



- Put loops of fibre away as shown. Ensure fibre is stored below tabs.
- Expand the fibre coils using light finger pressure and close splice tray cover.

Copyright Prysmian Group - 2023 You may not copy, reprint, or reproduce in any form the content, either wholly or in part, of this Installation Guide, without the written permission of the copyright owner. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend the information within this Installation Guide without prior notice. This Installation Guide may include inaccuracies, omissions of content and of information and is not contractually valid unless specifically authorised by Prysmian Group. Property of Prysmian Group UK - Uncontrolled when printed Prysmian Cables & Systems Limited, Chickenhall Lane, Eastleigh, Hampshire, SO50 6YU, United Kingdom.

PRYSMIAN HELPLINE: + 44 (0) 7816191633
connectivity.help@prysmiangroup.com